

CAM2[®]
INTERNATIONAL, LLC

CAM2 Blue Blood Racing Oils



CAM2 Blue Blood Racing Oils SAE 50 High Zinc Formula Product Code #600

The CAM2 Racing Heritage goes back to 1966 and the successful Roger Penske/Sunoco Racing program. The award winning CAM2 chemistry in the 20W-50 formula was developed as a three-way venture between Sunoco, General Motors and Penske racing. Using CAM2 racing motor oils race teams competed and won in Trans Am, Can Am, CART Championship (Indy Cars) and NASCAR. Using CAM2 motor oils Penske Racing won at Indy on three occasions with Rick Mears and Bobby Unser. CAM2 racing motor oil was the first multiviscosity oil to win at Indy.

Today, World class racers like Grave Digger, the most widely recognized Monster Truck in the world, Sheltra Motorsports who competes in the Nationwide[®] and ARCA[®] series, and Kevin Mayer's Pirate Ship PRO-MOD Willys use High Zinc CAM2 Blue Blood Racing Motor Oils, Gear Oils, Grease and Transmission Fluids because they know they can depend on CAM2's race proven performance oils for maximum protection under even the most extreme high load and pressure conditions.

- High Zinc levels for Excellent Anti-Wear Protection
- 0W-30 is a Full Synthetic Racing Oil
- 10W-30 and 20W-50 Racing Oils are Synthetic Blends
- Top of the line shear stable VI improvers, for stay in grade performance.
- Excellent oxidation stability in high performance engines
- Break-In Oil for optimal start-up protection

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2



CAM2 Blue Blood Racing Oils

CAM2 Blue Blood Racing Oils

High Zinc Formula

CAM2 BLUE BLOOD RACING OILS are available in 3 multi-viscosity grades. The 0W-30 is a Full Synthetic Formulation, The 10W-30 and 20W-50 are formulated in combination with synthetic base oil to provide enhanced protection at high and low temperature extremes. SAE 50 and "Nitro" SAE 70 is specifically formulated for gas, alcohol and nitro-methane fueled racing engines that experience extreme load and high temperature conditions. The high viscosity of the oil allows for excessive dumping of fuel "blow by" into the racing oil while maintaining critical protection.

CAM2 Hi-Performance Break-In Oil has a high level of performance additives to insure excellent anti-wear performance and protection during the initial start up and break in of new engines. This highly increased amount of zinc, phosphorus and sulfur chemistries is formulated to facilitate optimal ring seal and protect rotating assembly components such as the camshaft and valve train from initial start up wear. CAM2 Hi-Performance Break-In Oil optimizes the anti-wear protection required in flat-tappet and roller engines. Additionally, maximum compression is provided along with maximum horsepower being generated. Our proprietary formula requires no additional additives.

AVAILABILITY

CAM2 BLUE BLOOD RACING OILS are available throughout the U.S. and Internationally

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

Revised 5/15/2010



INTERNATIONAL, LLC

CAM2 Blue Blood Racing Oils

TYPICAL PROPERTIES - CAM2 BLUE BLOOD RACING OILS

SAE GRADE:	Test Method	0W-30	10W -30	20W-50	NITRO 70	SAE 50	Break-In Oil
		675	676	677	678	600	631
API Gravity, 60° F	ASTM D-1298A	33.1	31.5	30.2	27.1	27.2	30.9
Specific gravity	Calculated	0.86	0.868	0.875	0.892	0.891	0.871
VISCOSITY cSt@40°C	ASTM D-445	53.8	76.8	150	360	227.7	94.89
cSt@100°C	ASTM D-445	10	11.88	19.25	28.3	20.03	13.29
Viscosity, SUS @	ASTM D-2161	270	370	730	1,760	1055	440
Viscosity, SUS @	ASTM D-2161	59.5	66.8	101	138	98.6	71.3
Viscosity Index	ASTM D-2270	173	150	146	107	101	140
CCS, cP	ASTM D-5293	5,800 @ (-35°C)	5,950 @ (-25°C)	6,400 @ (-15°C)	N/A	N/A	5,100 @ (-20°C)
MRV, cP	ASTM D-4598	22,500 @ (-40°C)	40,800 @ (-30°C)	36,500 @ (-20°C)	N/A	NA	40,000 @ (-25)
HTHS @150°C, cP	ASTM D-4683	3.38	3.54	6.2	N/A	> 3.7	> 3.7
Pour Point, °F (°C)	ASTM 5949	-60 (-51)	-44 (-42) (max)	-33 (-36)	21 (-6)	-18	-39
Flash Point, COC, °F (°C)	ASTM D-92	385 (196)	400 (204)	420 (216)	548° F	420 (216)	400 (204)
Calcium, ppm	ASTM D-6481	2,100	2,100	2,100	2,100	2,100	500
Zinc, ppm	ASTM D-6481	2,100	2,100	2,100	2,100	2,100	3,400
Phospho- ppm	ASTM D-6481	1,800	1,800	1,800	1,800	1,800	3,100
Color	ASTM D-1500	Blue	Blue	Blue	Un-Dyed	Un-Dyed	Un-Dyed
TBN	ASTM D-2896	9	10.6	10.6	9.5	10.6	N/A
Sulfated Ash, mass %	ASTM D-874	1.2	1.2	1.2	1	N/A	N/A
Sulfur, ppm		4,000 ppm	4,000 ppm	4,000 ppm	5,000 ppm	4,000 ppm	11,500ppm

Contact your CAM2 representative or CAM2 distributor for additional information.

PRODUCT BULLETIN

www.CAM2.com
800-338-CAM2

Revised 5/15/2010